

## // 620AA

**Fuel-oil S&D 20 bar (300 psi)**

**Tube:** black conductive NBR.

**Reinforcement:** high tensile textile cords with embedded steel helix wire - antistatic wire.

**Cover:** black CR - abrasion, ozone and hydrocarbon resistant.

**Application:** fuel and oil suction and delivery.

Designed for long service life in heavy duty applications.

**Temperature:** -30 °C +80 °C (-22 °F +176 °F)

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (bar)	BP (psi)	BR (mm)	BR (in)	Vacuum %	Weight (kg/m)	Weight (lb/ft)
51,0	2"	63,0	2,48	20	300	60	900	204	8,03	100,00	1,660	1,12
63,0	2 1/2"	77,0	3,03	20	300	60	900	252	9,92	90,00	2,150	1,45
76,0	3"	90,0	3,54	20	300	60	900	304	11,97	90,00	2,660	1,79
102,0	4"	118,0	4,65	20	300	60	900	408	16,06	90,00	3,630	2,44
127,0	5"	145,0	5,71	20	300	60	900	508	20,00	80,00	6,120	4,12
152,0	6"	172,0	6,77	20	300	60	900	608	23,94	80,00	8,310	5,59
203,0	8"	225,0	8,86	20	300	60	900	812	31,97	70,00	12,400	8,34