

Dimensions shown may be changed without prior notice

// 976AB



General purpose 20 bar (300 psi) - EPDM

Tube: black conductive EPDM.

Reinforcement: high tensile textile cords.

Cover: grey EPDM - abrasion and ozone resistant.

Application: air, water and mild chemicals delivery in general industrial applications.

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

↔		↔		↙		↘		↵		%	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in		kg/m	lb/ft
6,0	1/4"	13,00	0,51	20	300	60	900	40,0	1,57		0,160	0,11
8,0	5/16"	15,00	0,59	20	300	60	900	50,0	1,97		0,200	0,14
10,0	3/8"	17,00	0,67	20	300	60	900	60,0	2,36		0,220	0,15
13,0	1/2"	21,00	0,83	20	300	60	900	75,0	2,95		0,340	0,23
16,0	5/8"	25,00	0,98	20	300	60	900	95,0	3,74		0,450	0,31
19,0	3/4"	29,00	1,14	20	300	60	900	100,0	3,94		0,570	0,39
25,0	1"	35,00	1,38	20	300	60	900	120,0	4,72		0,740	0,50

// 956AB



General purpose 20 bar (300 psi) - EPDM

Tube: black conductive EPDM.

Reinforcement: high tensile textile cords.

Cover: grey EPDM - abrasion and ozone resistant.

Application: air, water and mild chemicals delivery in general industrial applications.

Constant operation: -40 °C +100 °C (-40 °F +212 °F)

↔		↔		↙		↘		↵		%	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in		kg/m	lb/ft
32,0	1 1/4"	44,00	1,73	20	300	60	900				0,920	0,62
38,0	1 1/2"	52,00	2,05	20	300	60	900				1,080	0,73
51,0	2"	66,00	2,60	20	300	60	900				1,650	1,11