

## Flenzen & Lasfittingen / Blindflenzen

Type:	Blindflens, Type 05A
Kwaliteit	S235JRG volgens EN1092-1
Incl.	3.1 certificaten

DN	Art. Code	Druktrap	INCH	Buis (mm)	D (mm)	C4 (mm)	k (mm)	Aantal gaten	L (mm)	Gewicht kg/st
DN 15	050-02-015	PN10/40	1/2"	21,3	95	16	65	4	14	1,00
DN 20	050-02-020	PN10/40	3/4"	26,9	105	18	75	4	14	1,00
DN 25	050-02-025	PN10/40	1"	33,7	115	18	85	4	14	1,50
DN 32	050-02-032	PN10/40	1.1/4"	42,4	140	18	100	4	18	2,00
DN 40	050-02-040	PN10/40	1.1/2"	48,3	150	18	110	4	18	2,50
DN 50	050-02-050	PN10/40	2"	60,3	165	18	125	4	18	2,44
DN 65	050-02-065-4	PN10/16	2.1/2"	76,1	185	18	145	4	18	3,50
DN 65	050-02-065-8	PN10/16	2.1/2"	76,1	185	18	145	8	18	3,50
DN 80	050-02-080	PN10/16	3"	88,9	200	20	160	8	18	4,50
DN 100	050-02-100	PN10/16	4"	114,3	220	20	180	8	18	5,50
DN 125	050-02-125	PN10/16	5"	139,7	250	22	210	8	18	8,00
DN 150	050-02-150	PN10/16	6"	168,3	285	22	240	8	22	10,50
DN 200	050-02-200	PN10	8"	219,1	340	24	295	8	22	16,50
DN 250	050-02-250	PN10	10"	273,0	395	26	350	12	22	24,00
DN 300	050-02-300	PN10	12"	323,9	445	26	400	12	22	31,00
DN 350	050-02-350	PN10	14"	355,6	505	26	460	16	22	39,50
DN 400	050-02-400	PN10	16"	406,4	565	26	515	16	26	49,50

